



Moose Sports Surfaces, Ltd.
2257 North Wayne Avenue, Suite 2C
Chicago, Illinois 60614
773.477.4664
773.477.8248 *fax*
www.mooseports.com

SPORTLASTIC®
CARE & MAINTENANCE GUIDE
Revised 04-17-09

- 1) Regular floor maintenance is recommended; daily sweeping is suggested especially for high traffic areas.
- 2) Additionally, regular washing is recommended depending on programs being performed on the surfaces. Washing detergent must be a mild non-phosphate type with neutral pH such as Taski Profi supplied by Johnson-Diversey.
- 3) Surface should be vacuumed of all loose dirt from the floor prior to washing.
- 4) Soft nylon brushes are recommended when washing. The use of an Auto-scrubber with cylindrical brush is ideal.
- 5) Solution should set for approximately 10 minutes before you vacuum up the solution. Heavily soiled areas may need to be scrubbed twice. **DO NOT** allow the cleaning solution to dry onto the floor.
- 6) Use fresh water to rinse the floor of any residue left behind. This procedure may need to be done more than once until all residue is removed.
- 7) Protect your surface when moving heavy equipment. Always use plywood to protect the surface, especially when allowing vehicles on surface. Please make sure all equipment is in good working order to avoid any oil or gas spills.
- 8) All food and drink should be prohibited on the surface.
- 9) Recommended maintenance equipment includes:
 - Vacuum
 - Sweeper (Walk Behind)
 - Auto – Scrubber
 - Brooms, pails, etc.