



**Moose Sports Surfaces, Ltd.**  
 2257 North Wayne Avenue, Suite 2C  
 Chicago, Illinois 60614  
 773.477.4664  
 773.477.8248 fax  
 www.mooseports.com

**XTREMETILE®**  
**SYNTHETIC FLOORING CARE & MAINTENANCE GUIDE**  
**Revised 06-17-11**

The XTREMETILE® synthetic flooring system, like all quality floor surfaces, requires consistent cleaning and scheduled maintenance to ensure that it stays looking great. The schedule for cleaning depends on many factors including – various activities, how often the floor is used, and the volume of foot traffic on the floor. The more consistent the cleaning schedule, the better the appearance of the floor. The following general guidelines will help to keep your new XTREMETILE® floor looking great.

PRODUCTS AVAILABLE FOR PURCHASE TASKI® products available from JohnsonDiversey. Call 1-800-827-5427 or visit [www.johnsondiversey.com](http://www.johnsondiversey.com).

Steps	Cleaning Product	Mixture	Equipment
Initial Cleaning	TASKI® profi	10 oz./gal. water	Purple Pad or soft nylon brush
Daily Cleaning	TASKI® profi	6-10 oz./gal. water	Purple Pad, soft nylon brush or microfiber mop
Heavy Soil & Restorative Cleaning	TASKI® profi or TASKI® ice it	10 oz./gal. water	Purple Pad or black pad

The application rates and concentrations are based on TASKI® recommendations. For rates and concentration of other products, consult the specific manufacturer's instructions.

**1. Initial Cleaning**

- 1) Remove all surface soil, debris, sand and grit by sweeping, dust mopping or vacuuming with a high CFM vacuum. For large areas, use auto scrubbers to clean floors.
- 2) Scrub floor with a neutral pH (7-9) detergent, such as TASKI® profi cleaner (10 oz./gal. of water), using buffer or auto scrubber with a soft nylon brush or a purple pad. Avoid flooding the floor.
- 3) Pick up solution with a wet vacuum, rinse with clean water, picking up the rinse water with a wet vacuum, and allow to dry thoroughly (6-8 hours).

**2. Daily/Regular Cleaning**

- 1) Sweep, dust mop or vacuum floor to remove surface soil, debris, sand and grit.
- 2) Damp mop with a microfiber mop or auto scrub using TASKI® purple pad with TASKI® profi (6-10 oz./gal. of water) or equivalent pH neutral cleaner.

**3. Restorative Maintenance**

- 1) Sweep and dry vacuum floor thoroughly.
- 2) Heavy scrub floor with TASKI® profi (10 oz./gal. of water) or TASKI® ice-it. This cleaning may be performed with an auto-scrubber or rotary scrubber (TASKI® purple or black pad).
- 3) Vacuum soiled solution with a wet/dry vacuum.

- 4) Rinse with clean water.
- 5) Pick up solution with wet vacuum.
- 6) Allow floor to thoroughly dry.

#### **4. Heavy Soil**

- 1) Remove as much surface soil, debris, sand and grit as possible by sweeping, dust mopping or vacuuming.
- 2) Scrub floor with a neutral pH (7-9) detergent, such as TASKI® profi cleaner or TASK®I ice it stripper, using a buffer or auto scrubber with a TASKI® black pad.
- 3) Pick up solution with a wet vacuum, rinse with clean water and allow to dry thoroughly (6-8 hours).