



MOMENTUMXT® **CARE & MAINTENANCE GUIDE**

MomentumXT® rubber flooring is a 100% synthetic rubber floor product, formulated with the finest materials and manufactured with the most advanced process. It has been developed to render long term service, while offering a permanently resilient surface.

In order to receive full value, it is important that proper maintenance procedures are followed.

CAUTION

1. Allow 72 hours for the adhesive to cure prior to the cleaning of the floor. If any adhesive is on the floor it should be removed as soon as possible, before the adhesive starts to cure.
2. Do not use steel wool or abrasive pads; this will permanently damage the surface. A general dullness may result from the process of removing adhesive from the surface. If the natural luster does not return, the floor may have to be cleaned and an application of floor finish may be necessary.
3. **DO NOT USE STRONG SOLVENT CLEANERS (i.e. Lestoil, Top Job, Pinesol or similar products), GASOLINE, TURPENTINE or ACETONE. THE USE OF THESE PRODUCTS CAN CAUSE PERMANENT DAMAGE.**
4. **DO NOT USE SCRUBBING PADS or DISKS.**
5. **DO NOT USE BLACK, BROWN, GREEN, or BEIGE PADS.**
6. **DO NOT USE HIGH SPEED BUFFING MACHINES OR SCRUBBERS ABOVE 350 RPM.**
7. **DO NOT USE HIGH ACRYLICS FINISH MATERIAL.**
8. **DO NOT LET WATER STAND (PUDDLE) ON THE MATERIAL.**

INITIAL CLEANING

1. Wait 72 hours after installation before proceeding with floor maintenance.
2. Sweep or vacuum the entire floor surface to remove all loose dirt, dust and foreign objects.
3. Use REBOUND www.reboundusa.com. Washing detergent must be a mild non-phosphate type with neutral pH. Follow the manufacturer instructions.
4. To avoid excessive suds, pour cleaner into water rather than adding the water to the cleaner.
5. Blockade areas to be cleaned, as floors will be very slippery until dry.
6. Pick up soil and excess cleaner with a tightly wrung-out cleaning mop.
7. Do not rinse floor after cleaning.
8. Let floor dry completely.

DAILY MAINTENANCE

1. It is recommended to sweep and/or dust mop or vacuum (with heavy-duty commercial vacuum) the floor to remove all dirt and grit daily. This is the single most important maintenance activity for preserving the floor's appearance and performance – and typically the most overlooked and omitted.

WEEKLY MAINTENANCE

1. The floor should be cleaned as follows AT LEAST weekly. The frequency of washing depends on traffic, the number of programs and special events on the surface. It is recommended that the entire surface be washed on a regular basis.
2. Sweep/vacuum flooring to remove all loose dirt and debris.

4. Clean the MomentumXT® weekly (or more if needed) with REBOUND www.reboundusa.com. Using an auto-scrubber equipped with soft nylon brushes, apply the neutral cleaner using the manufacturer's instructions.
5. For smaller areas, cleaning can be done by hand with mop, soft brushes, or wringer buckets. For larger areas use auto-scrubbers that wash and dry the floor with a soft brush or soft bristle attachment.
6. Extract wet residue with wet/dry vacuum, mop or auto-scrubber.
7. Repeat cleaning process as necessary to remove any remaining mold release or dirt.

AGGRESSIVE CLEANING

1. If the MomentumXT® floor is not maintained regularly, an aggressive cleaning may be necessary.
2. For aggressive cleaning, again use REBOUND www.reboundusa.com, but apply solution to approx 200-500 SF of the floor and allow to sit for approximately 10-15 minutes. Go back and scrub with soft nylon brush or bristle attachment.
3. Remove solution via mop, wet vac or auto-scrubber.
4. Continue in this manner until entire floor is done.
5. Rinse/scrub entire floor with water only to finish. Repeat rinsing as required to remove all residues. Note: The appearance of a white film following washing and rinsing is an indication that the rinsing procedure was not adequate, in such cases, repeat the rinsing procedure until the residue has been removed

BUFF CLEANING

1. Mopping without a brushing action can result in the buildup of material and soap residue, giving the surface a dull appearance.
3. Only buff MomentumXT® when it is 100% clean.
4. Using a .028 gauge flagged nylon or equal Union Mix, the floor can be dry buffed to achieve a higher luster. It is recommended to have an extra set of brushes to be used exclusively for dry buffing.
5. After buffing, the floor may be finished using TASKI Vision Matte (please follow the manufacturer instructions carefully before applying this maintenance coating).
6. Re-clean those areas where any old maintenance coating remains before applying any new maintenance coating. Apply the maintenance coating as instructed on the label by the manufacturer. Allow the finish to completely set prior to putting the area back in service.

GUM REMOVAL

1. Spray commercial gum removal solvent on the gum only, or use an ice pack to freeze the gum.
2. Remove the gum with a wooden or plastic spatula.
3. Remove residue of the gum with mineral spirit.
4. Clean area and hand buff with soft cloth or towel.

THESE INSTRUCTIONS AND RECOMMENDATIONS HAVE BEEN PREPARED TO ADVISE AS TO THE PROPER METHODS TO CLEAN YOUR FLOORING PRODUCT. MOOSE SPORTS SURFACING OR THE LOCAL DISTRIBUTOR CANNOT ACCEPT ANY RESPONSIBILITY FOR THE APPLICATION OF THESE INSTRUCTIONS OR RECOMMENDATIONS. IF THERE ARE ANY QUESTIONS IT IS IMPORTANT THAT, PRIOR TO THE ACTUAL CLEANING OR FINISHING OF THE PRODUCT, YOU CALL OUR OFFICE FOR FURTHER INFORMATION. PROPER MAINTENANCE IS NECESSARY IN ORDER FOR THE LIMITED WEAR WARRANTY TO BE IN EFFECT.